

CENTER 211 TRUE RMS CLAMP METER

FEATURE

- TRUE RMS
- Autoranging
- Auto Power Off
- High Speed Bargraph
- Measuring Range 1000A
- With 0.01A High Resolution
- REL Function
- MAX MIN Function
- DATA HOLD Function
- 1ms PEAK HOLD Function
- IEC 1010 600V CAT III, 1000V CAT II

GENERAL SPECIFICATIONS

Display: 3-3/4 digital LCD, 4000 count.

Sampling Rate: Digital: 2 Times/sec

Analog Bargraph: 20 Times/sec

Low Battery Indication: The  is displayed.

Auto Power Off: 30 minute

Battery Type: 9V, (6F22, JIS 006P, NEDA 1604)

Battery Life: 120hr approx.

Operating Temperature: 0°C to 40°C

Storage Temperature: -10°C to 60°C

Dimensions: 242(L) × 66(W) × 36(H)mm

Weight: Approx. 400g

Accessories: Carrying case, Battery, Instruction Manual & Test Lead.

ELECTRICAL SPECIFICATIONS

Function	Range	Resolution	Accuracy
ACA	40A	0.01A	±1.9%rdg+5dgt
	400A	0.1A	
	1000A	1A	
ACV	400V	0.1V	±1.2%rdg+5dgt
	750V	1V	
DCV	400V	0.1V	±0.75%rdg+2dgt
	1000V	1V	
Ohms	400Ω	0.1Ω	±1%rdg+2dgt
	4000Ω	1Ω	
·)))	·)))	Active Sound Level: ≤100Ω	
→	→	Test Current: 0.6mA	
Hz(A)	4KHz	1Hz	±0.3%rdg+1dgt
	10KHz	10Hz	
Hz(A)	4KHz	1Hz	±0.3%rdg+1dgt
	10KHz	10Hz	



Jaws Opening Diameter: 35mm

1ms Maximum PEAK Hold
1ms Minimum PEAK Hold

0.01A High Resolution



* The specifications and other information in this catalogue are subject to change without prior notice.

CENTER
CENTER TECHNOLOGY CORP.