

CENTER 222 MINI AC/DC CLAMP METER

FEATURE

- Pocket Size
- 4 digits Display
- Peak Hold Function
- Data Hold Function
- 0.1A Resolution at Full Range
- Touch Zero Function
- Auto Power Off

GENERAL SPECIFICATIONS

Numerical Display: 4 digital liquid crystal display

Sampling Rate: 2 Times/sec

Low Battery Indication: The  is displayed.

Battery Life: 80 hr approx. (alkaline)

Battery Type: 1.5V, Size AAA battery × 2

Auto Power Off: 30 minute

Operating Temperature: 0°C to 40°C

Storage Temperature: -10°C to 60°C

Dimensions: 187(L) × 50(W) × 29(H)mm

Weight: Approx. 220g

Jaw Opening Diameter: Cables 25mm

Accessories:

Carrying case, Battery, Instruction Manual and Test Lead

ELECTRICAL SPECIFICATIONS

Function	Range	Resolution	Accuracy
DCA	600A	0.1A	$\pm 2.5\% \text{rdg} + 10 \text{dgt}$
ACA	600A	0.1A	$\pm 2\% \text{rdg} + 5 \text{dgt}$
ACV	600V	0.1V	$\pm 1.5\% \text{rdg} + 5 \text{dgt}$
DCV	600V	0.1V	$\pm 1\% \text{rdg} + 2 \text{dgt}$
Ohms	1000Ω	1Ω	$\pm 1\% \text{rdg} + 2 \text{dgt}$
·)))	·)))	Active Sound Level: $\leq 100 \text{dB}$	

Peak Hold Capture Time: 10 ms



* The specifications and other information in this catalogue are subject to change without prior notice.

CENTER®
CENTER TECHNOLOGY CORP.